

KR545T Tabber

Meet the USPS specifications for self-mailers and booklet tabbing with Kirk-Rudy's proven all in one tabbing innovation... KR545T!

Applies tabs to 3 sides in a single pass to meet the new USPS specifications for self-mailers and booklet tabbing regulations.

- Innovative trailing edge tab application (patent pending)
- Servo driven web and trailing edge kicker
- Eliminate multiple equipment setup

The **KR545T** handles large 18" diameter rolls and runs all major types of tabs as well as pressure sensitive stamps and labels of various shapes and sizes. Multiple tabs or labels can be applied in a single pass.

The **KR545T**'s innovative dual web design allows inline operation with standard addressing and binding systems. Use with the **KR565 Roll Splice Unit** for uninterrupted continuous tabbing and labeling.

Tab
Lead-Edge,
Trail-Edge &
Side-Edges
All in a single pass
Regardless of product
orientation!



** Guards may have been removed for clarity; Do not operate machine without guards in place.

KR545T

Tabber

** General Specifications

Physical

	English	Metric
Length	100"	254 cm
Width	38"	96.5 cm
Height	78"	198.1 cm
Crated Weight	1200 lbs	544 kg

Electrical Requirements

Voltage	Amps	Phase	Hz
220 VAC	50	1	Single Phase 50/60 3-Wire

Compressed Air Requirements

80 psi	at 4.0 SCFM
--------	-------------

Products

Tabs	Min 0.50" dia. (1.27cm)	Max 1.5" dia. (3.81 cm)
Tab Quantity	1 to 6 Tabs or Stamps	
Reel Capacity	18" (45.7 cm)	
Tab Accuracy	+/- 0.0625" (1.6 mm)	
Labels	3" (7.62cm) W x 6" (15.24cm) L standard	
Materials	Minimum: 3.50" W (8.9 cm) 3.50" L (8.9 cm) .008" (0.2 mm)	Maximum: 11" W (27.9 cm) 11" W (27.9 cm) .25" T (6.3 mm)

Operating Speeds

Maximum	350 fpm (138 mpm)
---------	-------------------

Note: Speeds are dependent on material being fed

Features & Benefits

- Servo driven controls
- Side register belts for tight tabs
- Touch screen tab location feature
- Side to side tabletop adjustment
- Industry standard motors and control
- Quick release upper belt system
- Quick release peel plates
- Runs in-line with most addressing and bindery systems
- Stop-out stop-in electrical interface
- KR conveyor pass through controls

Options

- Third Web 5" Wide Label Kit available upon request
- Single Crank Hydraulic Lift Kit for height adjustment up to 5 inches
- Vacuum Web Waste Removal Kit
- Bump Turn Kit for infeed table section
- Knife Web Waste Removal Kit

Supporting Equipment

- KR496F Friction Feeder
- KR415 Bump Turn Interface Conveyor
- KR565 Label Splicing Unit with continuous feed for uninterrupted tabbing and labeling

**Specifications subject to change with out notice



www.cess.com.mx
info@cess.com.mx
+52(55) 5286-4122

CESS MAILING + FULFILLMENT